

## NIC500SCEB

Ice Cream Freezer



### Product features

- NEW: Includes full set of baskets
- Curved sliding lids with lock
- Digital thermometer
- Powder coated white steel inner liner
- Castors with brake



White coated steel inner liner



Digital thermometer

### Elegant chest freezer with curved sliding glass lids

The NIC-SCEB range is a compact display chest freezer in an elegant design. It has curved corners, rounded edges and curved sliding glass lids.

It is a very stable and solid build, but at the same time on wheels so that it is easy to change location in the shop.

It comes in many sizes, which makes this model perfect for smaller shops and delis with limited space as well as lager shops, gas stations, supermarkets etc.

All sizes are environmental friendly and can be branded for better presentation of the cabinet content.

The SCEB-range is with a lower front than back and curved sliding glass lids. Both features provides a better visual display and presentation of the content. This makes the freezer ideal for display of frozen food including ice cream and lollies. Temperature can be held around -14°C for ice cream or around -21°C for other frozen foods.

All sizes have glass lids with a lock for security. They also have a defrost drain for cleaning out the unit.

Design and Material	
Tempered glass	Yes
Number of lids	2
Lid No & Type	2 curved sliding glass lids
No. of baskets	6
Basket No & Type	6 Wire basket, white
Castors	4 wheels, 2 with brake
Exterior Finish	White
Interior Finish	White painted steel
Lock	Yes

Measures and Content		
Temperature Range	°C	-24 to -14
Climate Class		5
Gross / Net Weight	kg	122 / 110
Gross / Net Volume	l	475 / 367

Cooling and Functions		
Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R290
Refrigerant Charge	g	110
Thermometer		Yes
GWP		3

Power and Consumption		
Energy Class		F
Energy Arrow		
Energy Consumption	kWh/24h	4
Annual Energy Consumption	kWh/year	1460
EEl		72,9
EEl Vol	l	352
Input Power	W	191
Voltage / Frequency	V/Hz	220-240/50
Noise Level	db(A)	45

Dimensions		
Internal Dimension (WxDxH)	mm	1430 x 510 x 571

Power and Consumption		
External Dimension (WxDxH)	mm	1570 x 650 x 918
Packed Dimension (WxDxH)	mm	1640 x 765 x 990
40ft Container Load	pcs	42