



LPD1200C/BLACK

Refrigerated Display Counters

Product features

- Stainless steel and gloss black glass frame
- LED light under each shelf
- Adjustable shelves (one step)
- Rear glass sliding doors
- Adjustable feet and castors
- Curved top/glass top/front
- Ventilated cooling
- Double glazed glass
- Anti mist front glass



Pastry display



Sliding doors

Design and Material		Measures and Content		Power and Consumption	
No. of Doors	2	Temperature Range °C	+2 to +8	Energy Class	D
Door No & Type	2 sliding glass doors	Climate Class	3	Energy Arrow	
Tempered glass	Yes	Gross / Net Weight kg	309 / 269	Energy Consumption kWh/24h	12,58
No. of Shelves pcs	3	Gross / Net Volume l	328 / 218	Annual Energy Consumption kWh/year	4592
Shelves No & Type	3 glass shelves + base	Total Display Area m²	2,01	EEl	38
Shelf Dimensions	105x23 / 105x28 / 105x33 / 105x44	Cooling and Functions		Input Power W	580
Feet / Legs	4 adjustable feet	Type of Controller	Electronic	Voltage / Frequency V/Hz	220-240/50
Castors	4 castors	Type of Cooling	Ventilated	Noise Level db(A)	48
Exterior Finish	Stainless steel / Glass	Type of Defrost	Automatic	Dimensions	
Interior Finish	Stainless steel / Glass	Refrigerant	R290	Internal Dimension (WxDxH) mm	1050 x 580 x 780
Interior Light	LED	Refrigerant Charge g	130	External Dimension (WxDxH) m	1205 x 745 x 1360
		Thermometer	Yes	Packed Dimension (WxDxH) m	1260 x 800 x 1480
		GWP	3	40ft Container Load pcs	23