TEFCOLD®

COOL PRODUCTS WORLDWIDE

FSC1000H BLACK

Black Display Cooler

Product features
• Illuminated canopy
• Internal vertical light
• Black interior and exterior
• Adjustable shelves
• Adjustable feet
• Ventilated cooling
• Hinged alu-framed glass doors

LED light

33 cl	50 cl	33 cl	50 cl
1066	754	520	520

Black 2-door display cooler with canopy

The FSC range is with a light canopy. The possibility for customized branding is eye-catching and stimulate impulse sales. The unit keeps beverages cold whilst presenting and promoting the products to their best advantage.

This model is with black exterior and interior. The black exterior finish looks great, the black interior makes the content stand out - especially with LED lights perfectly illuminating the content. It is ideal for high-end cafes, delis, patisseries and in-store placement in supermarkets.

It comes with 5 adjustable black wire shelves, 2 self-closing hinged glass doors, 2 vertical full length LED lights inside the door frame and a LED light canopy.

Design and Material

No. of Doors	2
Door No & Type	2 hinged glass door
Door Reversible	No
No. of Shelves pcs	5
Shelves No & Type	5 wire shelves black
Shelf Color	Black
Shelf Dimensions	870 x 540 mm
Canopy Type	L-Shape
Canopy Light	LED
Feet / Legs	4 adjustable feet
Castors	4 rollers
Exterior Finish	Black
Interior Finish	Black RAL9005
Interior Light	LED
Lock	Yes

Measures and Content

Cans 330 ml	pcs	1066
Cans 500 ml	pcs	754
Bottles 330 ml	pcs	520
Bottles 500 ml PET	pcs	520
Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	175 / 162
Gross / Net Volume	l	796 / 524

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	120
Thermometer		Yes
GWP		3

Power and Consumption

Energy Class		F
Energy Arrow		F A↑G
Energy Consumption	kWh/24h	5,96
Annual Energy Consumption	kWh/year	2175
EEI		76,5
EEI Vol	l	882
Power		
Max Ambient		30°C at 55% RH
Input Power	W	450
Voltage / Frequency	V/Hz	220-240/50
Noise Level	db(A)	48

Dimensions

Internal Dimension (WxDxH)	mm	890 x 670 x 1533
External Dimension (WxDxH)	m m	1000 x 790 x 2000

Power and Consumption		
Packed Dimension (WxDxH)	mm	1080 x 840 x 2100
40ft Container Load	pcs	28