



Blast Chiller

GBC05X



Label not required	Energy efficiency class	Item number	63328710000GBC05X	Taric goods code	84185019
	Label not required	EAN code	5704704016361	QTY in 40HQ	62


Short Description

Cycles can be controlled by time or by temperature according to the reading of the temperature probe inside the product. If no probe is in use, time control is applied automatically. Once chilling / freezing cycle is over, devices enter in standby mode, working as refrigerator keeping the temperature between +2 and +5° after chilling and below -18° after freezing cycle. "Ventilation gill" on the front panel to keep cooling unit system ventilated and working more efficiently. Automatic defrosting device and automatic, no energy consumption in the evaporation of condensation. Hinged door with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and closes automatically at less than 90°.

Key features

- Fast chilling +90°C to +3°C in 90 min
- Fast freezing +90°C to -18°C in 240 min
- Suitable for 5 pcs. GN 1/1
- Probe to monitor the temperature of the product
- Self-closing door with 120° dwell position
- AISI 304 stainless steel internally
- AISI 201 stainless steel externally
- Also available as 60 Hz for marine / offshore as an order item

Measurement Drawings



Dimensions and weight

Product dimensions, HxWxD, mm	850 x 790 x 700
Product depth w/handle, mm	700
Packaging dimensions, HxWxD, mm	1065 x 895 x 810
Total packaging volume m3	0,772
Gross volume, L	121
Net volume, L	103
Gross- / Net volume, L	121 / 103
Internal dimensions, HxWxD, mm	389 x 670 x 600
Gross- / Net weight, kg	105 / 101

Performance and consumption

Energy efficiency class	Label not required
Refrigeration / freezing technique	Ventilated
Climate class	4
Type of refrigerant / gas gr.	R452a / 600
Temperature range °C	+3 / -18
Energy efficiency class	-

Installation and power

Voltage / hertz, V/hz	230 / 50
Length of Powercord, cm	300

Design and comfort

Controller	Digital
Control panel	Outside
Digital display	Yes
Internal light	No light
External thermometer	Yes
Reversible door	Yes
Door- / lid type	Right hinged
Self closing door	Yes
Handle	Integrated
Number of feet	4
Number of castors, pcs	0
Lock & Key	No

Colour and material

Inside Colour	Stainless Steel
Colour and material of door/lid	Stainless steel solid

Interior features

Number of Shelves	0
Adjustable shelves	Yes

scandomestic

Scandomestic A/S . Linåvej 20 . DK-8600 Silkeborg . Tel.: +45 7242 5571 . www.scandomestic.dk